

ALIMAK SC45/30

Construction Hoist for Passengers and Materials



Access anytime, anywhere

ALIMAK SC45/30

Main Characteristics

- Compact design and comfortable operating environment
- Proven helical gearbox
- Single and dual car configurations
- Design without counterweight
- Multiple choices of doors
- Simple and easy operating system
- Recessed control panel
- PLC control as an option
- Durable materials: high quality steel for increased strength and weight reduction, hot dip galvanized mast section and tie-in
- Wide range of tie-in
- Wide range of optional equipment and functions



SC45/30	DOL	FC
Max. Payload capacity	2000 kg	2000 kg
Traveling speed	36 m/min	0 ~ 60 m/min
Max. Lifting height *	150 m	250 m
Car width, internal	1.4 m	1.4 m
Car length, internal	3.0 m	3.0 m
Car height, internal	2.13 m	2.13 m
Motor control	DOL	FC
No. of motors and power	2 x 8.5 KW	2 x 16.4 KW
Safety device type*	SAJ30-1.2 or Alimak GF	SAJ40-1.4 or Alimak GF
Dimension of Mast Section	450 x 450 x 1508 mm, tubular steel with integrated rack	450 x 450 x 1508 mm, tubular steel with integrated rack
Rack module	5	5

* Increased lifting height on request

* Alimak Safety device as an optional

Alimak Hek Vertical Access Equipment (Changshu) Co., Ltd.

Building 12, Ma Qiao Industry Square, Changshu Economic
Development Zone, Changshu 215513, China

Tel: +86 (0)512 5229 6800

Fax: +86 (0)512 5229 6900

www.alimakhek.com

Alimak Hek Vertical Access Equipment (Changshu) Co., Ltd is ISO 9001 certified.



Pictures are illustrative only and do not necessarily show the configuration of products on the market at a given point in time. Products must be used in conformity with safe practice and applicable, statutes, regulations, codes and ordinances. Specifications of products and equipment shown herein are subject to change without notice. Copyright Alimak Hek Vertical Access Equipment (Changshu) Co., Ltd. All rights reserved. Alimak Hek, Alimak and Scando are registered trademarks of Alimak Hek Group AB.